


OSIGHT SE MOS


Simple yet Extraordinary



Direct MOS
Slide Mount




Multi-Reticle
System



Side-Loading
CR1632 Battery



Aspherical Lens



Motion Sensor



Low Power
Indication



OSIGHT SE MOS

Simple yet Extraordinary

Market Applications

Tactical, Self-Defense, Everyday Carry, Training

UPC

6978095650384

DESCRIPTION


The Osight SE MOS is a premium enclosed-emitter pistol optic designed for full-size GLOCK® MOS pistols, featuring the industry's first direct MOS footprint for a lower-profile, adapter-free mount. Its fully enclosed emitter protects against dust, water, and debris for reliable performance in demanding conditions. The Multi-Reticle System offers a 2 MOA dot, 32 MOA circle, or dot-and-circle reticle for fast, versatile target acquisition, while the aspherical lens delivers exceptional clarity and parallax-free precision. A side-loading CR1632 battery enables easy replacement without removing the optic or losing zero. Motion activation, low battery warning, and brightness memory enhance convenience, while the low-deck height allows direct co-witness with most factory iron sights. CNC-machined from 7075-T6 aircraft-grade aluminum with 8 daylight and 2 night-vision brightness settings, the Osight SE MOS is built for tactical, defensive, and everyday carry applications.

Elevation Adjustment

Windage Adjustment



Battery Tray
(CR1632 Battery Included)



2 MOA Dot &
32 MOA Circle

Brightness Adjustment



FEATURES

- **Industry's First Enclosed Emitter Optic with Direct MOS Slide Mount:** The Osight SE MOS is the industry's first enclosed emitter optic engineered with a direct MOS footprint, eliminating the need for adapter plates on compatible full-size GLOCK® MOS slides. This streamlined design provides a lower-profile setup, improved fit, and fewer potential failure points. Combined with a fully enclosed emitter system, it protects against dust, water, and debris for uncompromising reliability in any environment.
- **Multi-Reticle System (2 MOA Dot & 32 MOA Circle):** Switch between dot-and-circle, 2 MOA dot-only, or 32 MOA circle-only reticles for any shooting scenario. Enjoy sharp clarity and strong contrast for precise, confident aiming.
- **Side-Loading CR1632 Battery:** Effortless battery replacement without removing the optic ensures hassle-free re-zeroing. A high-end CR1632 battery offers easy accessibility while maintaining steady performance.
- **Aspherical Lens:** The aspherical lens ensures zero distortion, parallax-free performance, and exceptional clarity for rapid, precise target acquisition.
- **Motion Sensor:** The Osight SE MOS powers on at the slightest movement, and powers down after 3 minutes of inactivity to conserve battery.
- **Low Power Indication:** When battery voltage drops below 2.2V, the reticle will quickly triple-flash once per minute to recommend a battery replacement.
- **Sleek Battery Tray:** With a sleek and streamlined battery tray design, the Osight SE MOS stays comfortable to carry, quick to draw, and ideal for concealed use.
- **Low-Deck Height:** The low-deck height provides a perfect co-witness with factory iron sights, eliminating the need for lower 1/3 or suppressor-height sights.
- **CNC-Machined Aircraft-Grade 7075-T6 Aluminum:** The optic is nearly indestructible with CNC-machined aircraft-grade 7075-T6 aluminum housing, ensuring durability and a professional edge over time.
- **10 Brightness Settings:** 8 daylight and 2 night vision settings — compatible levels for versatility in any demands.
- **Memory Function:** Once activated, the built-in memory function returns to the last selected brightness level, allowing users to focus on the target without distraction.

RUNTIME & BRIGHTNESS

Reticle			
Mode 3	86,900 H	140,000 H	93,000 H

Settings	Night Vision	Day Light
Brightness	(Lowest) Level 1-2	Level 3-10 (Brightest)

OSIGHT SE MOS

Simple yet Extraordinary

SPECIFICATIONS

Optic	Osight SE MOS
Reticle Type	2 MOA Dot & 32 MOA Circle
Reticle Color	Red
Emitter	Enclosed
Light Wavelength	650 nm
Adjustment Per Click	1 MOA
W&E Travel Range	± 35 MOA
Battery Life	140,000 H (Mode 3 Dot-only)
Power Source	CR1632
Brightness Settings	8 DL & 2 NV
Window Size	0.83 x 0.55 in 21 x 14 mm
Magnification	1x
Aspherical Lens	Yes
Parallax-Free	Yes
Unlimited Eye Relief	Yes
Motion Sensor Function	Yes
Memory Function	Yes
Multi-Coatings	Yes
Housing Material	CNC-Machined Aircraft-Grade 7075-T6 Aluminum
Waterproof Rating	IPX7
Dimensions	2.44 x 1.02 x 1.10 in 62 x 26 x 28 mm
Weight	1.59 oz / 45 g

⚠ WARNING


- **INGESTION HAZARD:** This product contains a button cell or coin battery.
- **DEATH** or serious injury can occur if ingested.
- A swallowed button cell or coin battery can cause **Internal Chemical Burns** in as little as **2 hours**.
- **KEEP** new and used batteries **OUT OF REACH** of **CHILDREN**.
- **Seek immediate medical attention** if a battery is suspected to be swallowed or inserted inside any part of the body.



WATERPROOF
IPX7



COMPLIANCE
CAN ICES-003 (B) / NMB-003 (B)



WARRANTY



www.osight.com/lifetime-warranty

IN THE BOX

Optic (CR1632 battery included)

Adjustment Tool

READ ME Card

3 x M3*8 mm Screws

2 x Spare Battery Compartment Screws

Screw Box

Osight Sticker

Cleaning Cloth

Safety Warnings

User Manual



Note: The Osight SE MOS MUST be mounted properly by applying non-permanent (medium/blue) threadlocker to the included screws. AND torque each screw to 15-17 in-lbs (suggested torque value in the READ ME card). If an adapter plate is required, please follow the manufacturer's installation instructions.



www.osight.com